



# FLATWORK DRYER IRONERS

Ø 200 MM

MICRAII



## ELECTRONIC CONTROL

Simple and user friendly: selection of ironing speed and temperature by push buttons



## EFFICIENCY

Good heat conduction thanks to the roll material and thickness: greater control of energy expenditure  
Automatic shutdown at 80°C  
Fumes circulation circuit from the bottom reducing energy consumption



## ROBUSTNESS

Roll driving by speed inverter  
Nomex quality feeding and ironing belts: high temperatures resistant



## ERGONOMICS

Acoustic comfort : <60 dB  
Appropriate operating height: 990 mm feeding belts  
Minimal encumbrance: space saving, suitable for most spaces




## MAINTENANCE

Easy access to all components on both sides of the machine  
Basic connections : electrical connection and air extraction  
Dimensions of all models without trays narrower than a door frame: 546 mm



## OTHERS

Dries and irons flat linen from a high spin washer extractor in a single operation  
Front feeding and return  
Built-in cool down system  
Polished steel roll Ø 200 mm  
Working width: 1400 mm  
Electric heating



## OPTIONS

- Marine tension 440V III 60 Hz without N
- Tension 230V III 50-60 Hz




Intertek



Intertek

TECHNICAL DATA	UNIT.	MICRAII
<b>GENERAL DETAILS</b>		
Theoretical production *	Kg/h	12-14
Theoretical production radiant gas *	Kg/h	-
Evaporation power	Kg/h	8-10
Ø Roll	mm	200
Working width	mm	1400
Height of feeding belts	mm	990
Ironing speed	m/min	1 - 5
Control		Electronic
No programs	N°	7
Rear exit + length folder		NO
<b>POWER</b>		
Electric heating	kW	10,5
Total electric power (Elec. model)	kW	10,84
Gas heating	kW	-
Total electric power (Gas model)	kW	-
Steam heating	kW	-
Total electric power (Steam model)	kW	-
Roll motor	kW	0,25
Fan motor	kW	0,09
Add. elec. power with folder	kW	-
Add. elec. power with folder + rear exit	kW	-
<b>CONNECTIONS</b>		<b>ELECTRIC</b> <b>GAS</b>
Tension 230V - III + T	N°x mm²/A	4x6 / 32A      -
Tension 400V - III + N + T	N°x mm²/A	5x4 / 20A      -
Ø gas inlet	BSP	-
Ø steam inlet	BSP	-
Ø condensed (steam model)	BSP	-
<b>DIMENSIONS / PACKING DIMENSIONS</b>		
Net width / Gross width	mm	1.878 / 2.130
Net depth / Gross depth	mm	444 / 770
Net height / Gross height	mm	1.335 / 1.570
Net weight / Gross weight	kg	180 / 220
Volume	m3	1,11 / 2,57
<b>OTHERS</b>		
No fume outlet	No	1
Ø Extraction	mm	83
Air flow	m3/h	300
Noise level	dB	55

\*45 %-25 % moisture



- 01. Electrical connection
- 02. Control panel
- 03. Emergency stop
- 04. Exhaust
- 05. Crank contactor
- 06. Crank
- 07. Main switch

	A	B	C	A1	B1	C1	D	E	F	G	H	I
MICRA II	1.885	448	1.335	1.878	444	1.110	Ø 83	1.020	1.000	635	21	-