



CHEST IRONERS

Ø 600 MM

SRC60-200 / 270 / 330

FEATURES

Roll size : ø 600 mm

Working widths: 2000, 2700 and 3300 mm

100 % carbon steel flexible chest raised by hydraulic actuators

Ironing surface until 185°

CONTROL

SIEMENS PLC microprocessor with a 4" color touch screen, easy to program and to use

Display of temperature and ironing speed

100 preset programs, creation of different ironing programs

Equipped with a smart-LED lighting system over the whole working width enlightening feeding bands and indicating the situation and status of the machine : error and technical indications

HEATING

Two modes of heating : electric or gas heating (natural gas as standard - type G20 / G25, LPG gas kit as option)

Indirect heating for both modes: thermal oil flows through the chest.

OTHERS

Rear exit of linen

Direct transmission by gear motor: no belts

Suction motor directly mounted on the roll



OPTIONS

- LPG gas Kit (propane G30 / butane G31)
- Front exit of linen
- Foot pedal for ironer start / stop
- L individual springs



Intertek



Intertek

TECHNICAL DATA	UNIT.	SRC60-200	SRC60-270	SRC60-330
GENERAL DETAILS				
Roll diameter ø	mm	600	600	600
Working width	mm	2000	2700	3300
Working speed (minimum)	m/min	2,4	2,4	2,4
Working speed (maximum)	m/min	14,4	14,4	14,4
Average output	kg/h	117	156	187
Rear exit		standard	standard	standard
Front exit		Option	Option	Option
Roll motor power	kW	1,5	1,5	1,5
Fume exhaust ø	mm	125	125	125
Fan power	kW	0,75	0,75	0,75
Flow rate	m ³ /h	1.240	1.240	1.240
Pressure	PA	100	100	100
HEATING				
GAS HEATING				
Nominal heating power	kW	55	73	88
Connection	inch	3/4"	3/4"	3/4"
Min-Max supply pressure	mbar	20/25/37 - 98		
Voltage		3 x 380 - 400 VAC - 50 Hz + N		
Cable		5G4		
Nominal tension		17,3 A		
ELECTRIC HEATING				
Voltage		3 x 380 - 400 VAC - 50 Hz + N		
Nominal heating power	kW	45	60	75
Cable		5G25		
Nominal tension		88,3 A	109,3 A	131,3 A
DIMENSIONS				
Net width	mm	3.112	3.812	4.412
Net height	mm	1.680	1.680	1.680
Net depth	mm	2.010	2.010	2.010
Transportation depth	mm	1.600	1.600	1.600
Depth without feeding / exit tables	mm	945	945	945
Net weight / Gross weight	kg	2.022 / 2.072	2.235 / 2.285	2.587 / 2.637