



WET LINEN TROLLEYS

CD-200/400/600FV
CD250/400/600PL -
CD-200/300/600FM

CD-200/400/600FV



- White fiberglass container
- Drain tap on 400 and 600 lt models
- 4 swivel wheels ø 100 mm



CD-200FV

CD-250/400/600PL



- Polyethylene construction on steel base
- Without tap
- 2 fixed and 2 swivel wheels ø 125 mm



CD-250PL

CD-200/300/600FM



- Anodized aluminium trolley
- Rubber bumpers
- Movable bottom to maintain a constant level of the plate whatever the load
- 2 fixed and 2 swivel wheels ø 100 mm



CD-200FM



Intertek



Intertek

TECHNICAL DATA	UNIT.	CD-200FV	CD-400FV	CD-600FV
Capacity	lt	200	400	600
Construction	-	Fiberglass	Fiberglass	Fiberglass
Wheels ø	mm	100	100	100
Dimensions	mm	560 x 655 x 715	550 x 865 x 735	700 x 1.000 x 740
Weight	kg	10	15	24

TECHNICAL DATA	UNIT.	CD-250PL	CD-400PL	CD-600PL
Capacity	lt	250	400	600
Construction	-	Polyethylene	Polyethylene	Polyethylene
Wheels ø	mm	100	100	100
Dimensions	mm	645 x 780 x 720	760 x 1.100 x 820	910 x 1.290 x 900
Weight	kg	15	24	40

TECHNICAL DATA	UNIT.	CD-200FM	CD-300FM	CD-600FM
Capacity	lt	200	300	600
Construction	-	Anodised aluminium	Anodised aluminium	Anodised aluminium
Wheels ø	mm	100	100	100
Dimensions	mm	1.030 x 450 x 800	1.030 x 630 x 800	1.390 x 675 x 800
Weight	kg	40	40	50